

# RONDA slimtech 1000

Extra small and slim movements  
for exclusive styles

*Caliber 1006 – 10½'''*



## Product Specifications

Analogue quartz movement	
Line	slimtech
Caliber	1006
Size	10½'''
Version	Swiss Made
	8 Jewels / gold plated
Standard battery life	25 months
High battery life	40 months
Hand fitting height	1

## Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Complete interchangeability between 1002-1009, 1012-1019

**Functions**

- 2 hands
- Date

**Technical Specifications**

Diameter Total	23.90 mm
Case fitting	23.30 mm
Movement height	1.90 mm
Height over standard battery	1.90 mm
Height over high battery	2.15 mm
Movement rest	0.35 mm
Height over stem	0.75 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Standard battery	341
High battery	315
Standard battery life	25 months
High battery life	40 months
Battery voltage	1.5 V
Current consumption – typical	0.74 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.1 µA (Date Mechanism not in Gear)
Useful torque minute – typical	200 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

**Watch production**

Drawing Casing ring (standard, PDF)  
 Drawing Casing ring (high battery, PDF)  
 Drawing Dial (stem 3h, calendar 3h, PDF)  
 Drawing Dial (stem 3h, calendar 6h, PDF)  
 Drawing Hand fitting (hand height 0-2, PDF)  
 Drawing Stem

**User's manual**

User's manual (PDF)

**Watch repairs**

Technical instruction (PDF)

