

RONDA normtech 700 & 6000

Lange Batterielaufzeit und spezielle Funktionen

Caliber 715Li – 11½'''



Product Specifications

Analog quartz movement

Line normtech

Caliber 715Li

Size 11½'''

Version Swiss Made 5 Jewels / gold plated
Swiss Parts 5 Jewels / nickel plated

Standard battery life 10 Years

Hand fitting height 1

Features

- Repairable metal watch movement
- Very long battery life
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Lithium battery

Functions

- Date
- 3 hands

Technical Specifications

Diameter Total	26.00 mm
Case fitting	25.60 mm
Movement height	4.60 mm
Height over standard battery	4.60 mm
Movement rest	0.60 mm
Height over stem	1.00 mm
Length of stem travel	0.90 mm
Stem thread	0.90 mm
Standard battery	CR2016
Standard battery life	10 Years
Battery voltage	3 V
Current consumption – typical	0.52 µA (Date Mechanism not in Gear)
Current consumption – maximum	0.7 µA (Date Mechanism not in Gear)
Useful torque second – typical	8 µNm
Useful torque minute – typical	400 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, calendar 3h, PDF)
 Drawing Dial (stem 3h, calendar 3h, round, PDF)
 Drawing Dial (stem 3h, calendar 4h, PDF)
 Drawing Dial (stem 3h, calendar 4h, round, PDF)
 Drawing Dial (stem 3h, calendar 6h, PDF)
 Drawing Dial (stem 3h, calendar 4 1/2 h, PDF)
 Drawing Dial (stem 3h, calendar 6h, round, PDF)
 Drawing Hand fitting (hand height 6, PDF)
 Drawing Hand fitting (hand height 0-5, PDF)
 Drawing Stem

User's manual

User's manual (PDF)

Watch repairs

Technical instruction (PDF)

