



**UNIQUE
BY SWISS DESIGN**



#rondamovement

 **RONDA**

RONDA startech 3500

Chronographs,
eye positions 6-9-12 and 6-12

Caliber 3540.D – 10½ x 11½'''



Product Specifications

Analog quartz movement

Line startech

Caliber 3540.D

Size 10½ x 11½'''

Version Swiss Made 5 Jewels / gold plated
Swiss Parts 5 Jewels / nickel plated

Standard battery life 54 months

Hand fitting height 1

Features

- Very long battery life
- Repairable metal watch movement
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Very easy handling by two pushers

Functions

- Chronograph
- Center stop second (1/1 sec)
- 1/10 seconds up to 30 minutes
- 30 minute counter
- 10 hour counter
- ADD and SPLIT functions
- 3 eyes
- Small second
- Date

Technical Specifications

Diameter Total	26.20 mm
Case fitting	23.90 mm
Movement height	4.90 mm
Height over standard battery	4.90 mm
Movement rest	0.80 mm
Height over stem	1.70 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Standard battery	384
Standard battery life	54 months
Battery voltage	1.5 V
Current consumption – typical	1.14 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.65 µA (Date Mechanism not in Gear)
Useful torque second – typical	6 µNm
Useful torque minute – typical	300 µNm
Useful torque center stop second – typical	6 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/+20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

- Drawing Casing ring (standard, PDF)
- Drawing Dial (stem 3h, calendar 3h, PDF)
- Drawing Hand fitting (hand height 1, PDF)
- Drawing Stem
- Casing information (PDF)

User's manual

- User's manual (PDF)

Watch repairs

- Technical instruction for code M (PDF)

