

# RONDA slimtech 1000

Extra small and slim movements  
for exclusive styles

*Caliber 1014 – 11½'''*



## Product Specifications

Analog quartz movement	
Line	slimtech
Caliber	1014
Size	11½'''
Version	Swiss Made
	10 Jewels / gold plated
Standard battery life	25 months
High battery life	40 months
Hand fitting height	1

## Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Complete interchangeability between 1002-1009, 1012-1019

**Functions**

- Small second
- 2 hands

**Technical Specifications**

Diameter Total	26.00 mm
Case fitting	25.60 mm
Movement height	1.90 mm
Height over standard battery	0.00 mm
Height over high battery	0.00 mm
Movement rest	0.35 mm
Height over stem	0.75 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Standard battery	341
High battery	315
Standard battery life	25 months
High battery life	40 months
Battery voltage	1.5 V
Current consumption – typical	0 µA
Current consumption – maximum	1.1 µA
Useful torque second – typical	4 µNm
Useful torque minute – typical	200 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

**Watch production**

Drawing Casing ring (standard, PDF)  
 Drawing Casing ring (high battery, PDF)  
 Drawing Dial (stem 3h, PDF)  
 Drawing Hand fitting (hand height 1-3, PDF)  
 Drawing Stem

**Watch repairs**

Technical instruction (PDF)

