



# RONDA startech 5000

Chronographs, Big Date & Date,  
different calendar systems, Alarm

*Caliber 5040.E – 12½'''*



## Product Specifications

Analog quartz movement	
Line	startech
Caliber	5040.E
Size	12½'''
Version	Swiss Made
Standard battery life	13 Jewels / gold plated
Hand fitting height	54 months
	1

## Features

- Hand Heights 1 and 2
- Very long battery life
- Repairable metal watch movement
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Very easy handling by two pushers

**Functions**

- Chronograph
- Center stop second (1/1 sec)
- 1/10 second
- 1/10 seconds up to 30 minutes
- 30 minute counter
- 10 hour counter
- ADD and SPLIT functions
- 3 eyes
- Day indicator
- Small second
- Date

**Technical Specifications**

Diameter Total	28.60 mm
Case fitting	28.00 mm
Movement height	4.40 mm
Height over standard battery	4.40 mm
Movement rest	0.60 mm
Height over stem	1.90 mm
Length of stem travel	0.90 mm
Stem thread	0.90 mm
Standard battery	395
Standard battery life	54 months
Battery voltage	1.5 V
Current consumption – typical	1.32 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.65 µA (Date Mechanism not in Gear)
Useful torque second – typical	6 µNm
Useful torque minute – typical	300 µNm
Useful torque center stop second – typical	7 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

**Watch production**

- Drawing Casing ring (standard, PDF)
- Drawing Dial (stem 3h, day straight 12h, date 6h, PDF)
- Drawing Hand fitting (hand height 1-2, PDF)
- Drawing Stem
- Casing information (PDF)

**User's manual**

User's manual (PDF)

**Watch repairs**

Technical instruction as of code W (PDF)

