

RONDA normtech 700 & 6000

Lange Batterielaufzeit und spezielle Funktionen

Caliber 756 – 5½'''



Product Specifications

Analog quartz movement

Line

normtech

Caliber

756

Size

5½'''

Version Swiss Made
Swiss Parts

4 Jewels / gold plated
1 Jewels / nickel plated

Standard battery life

7 Years

Hand fitting height

1

Features

- Very long battery life
- Electronic Time Setting:
 - brief pressure up to two seconds - minute correction
 - medium pressure between two and four seconds - hour correction
 - Pressure more than four seconds - continuous correction until corrector is released

Functions

- 2 hands
- Electronic time setting

Technical Specifications

Diameter Total	13.00 mm
Case fitting	13.00 mm
Movement height	3.10 mm
Height over standard battery	3.10 mm
Movement rest	0.40 mm
Height over stem	0.00 mm
Length of stem travel	0.00 mm
Stem thread	0.00 mm
Standard battery	379
Standard battery life	7 Years
Battery voltage	1.5 V
Current consumption – typical	0.34 µA
Current consumption – maximum	0.4 µA
Useful torque minute – typical	30 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10 / +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

- Drawing Casing ring (standard, PDF)
- Drawing Dial (Stem, PDF)
- Drawing Hand fitting (hand height 0-5, PDF)

User's manual

- User's manual (PDF)

