


RONDA slimtech 1000

Extra small and slim movements
for exclusive styles

Caliber 1032 – 3³/₄ x 6'''



Product Specifications

Analog quartz movement

Line slimtech

Caliber 1032

Size 3³/₄ x 6'''

Version Swiss Made 7 Jewels / gold plated
Swiss Parts 7 Jewels / nickel plated

Standard battery life 60 months

Hand fitting height 1

Features

- Do not pull stem during storage
- Repairable metal watch movement
- Very long battery life

Functions

– 2 hands

Technical Specifications

Diameter Total	9.00 mm
Case fitting	9.00 mm
Movement height	1.95 mm
Height over standard battery	2.10 mm
Movement rest	0.20 mm
Height over stem	0.62 mm
Length of stem travel	0.30 mm
Stem thread	0.70 mm
Standard battery	317
Standard battery life	60 months
Battery voltage	1.5 V
Current consumption – typical	0.25 µA
Current consumption – maximum	0.3 µA
Useful torque minute – typical	21 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

Drawing Casing ring (standard, PDF)

Drawing Dial (stem 3h, PDF)

Drawing Hand fitting (hand height 0-3, PDF)

Drawing Stem

Watch repairs

Technical instruction (PDF)

